



519.00 EUR

incl. 19% VAT, plus [shipping](#)

- HBJC143F693W-H110



- Intel® LGA1151 Socket Core i3,i5,i7 & Pentium Processors(max.65W)
- Support DDR4-2133Mhz, 2 * SO-DIMM slot, up to 32GB memory
- 2 * USB2.0, 4 * USB3.0, 1 * HDM , 1 * DP, 2 * RJ45, 1 * MIC, 1 * Line in, 1 * Line out
- M/B Form Factor : Mini ITX (170x170mm)
- 1U 200W FLEX Power

| | |
|-----------------|---|
| MB Model | - JNF693-H110 / Mini ITX |
| Part No | - HBJC143F693-H110-B (non-WIFI) - HBJC143F693W-H110-B (WIFI) |
| BIOS | - AMI 64MB SMT Flash ROM |
| CPU/Chipset | - INTEL® LGA1151 Socket Core i3, i5, i7 & Pentium Processors |
| Memory | - 2 * DDR4-2133 up to 32GB |
| Storage | - 2 * 2.5" or 1 * 3.5" SATA3 6Gb/s internal drive bay - 1 * M.2_SSD (M key-2242/2260) |
| Network | - 2 * Realtek® 8111H Gigabit LAN - 1 * Full-size mini-PCIE slot (802.11 b/g/n + BT 4.0 installed in WIFI model / Optional) |
| Rear Panel I/O | - 4 * USB 3.0 - 1 * HDMI (Max Resolution : 3840x2160@24Hz) - 1 * DP (Max Resolution : 4096x2304@60Hz) - 2 * RJ45 - 1 * Mic , 1 * Line in , 1 * Line-out (Realtek ALC662) - 6 * RS232 - 1 * AC -in CON |
| Front Panel I/O | - 1 * Power button - 1 * Power LED, 1 * HDD LED - 2 * USB 2.0 |
| Power Source | - 1U 200W FLEX POWER - AC 90~240V input |
| Compliance | - CE, FCC, LVDS, RoHS |
| Temperature | - Operating Temperature: 0 ~ 50° C - Storage Temperature: -10 ~ 70° C |
| Dimensions | - 330 (W) x 192 (D) x 44 (H) mm |
| Packing | - Net Weight: 2.0KG - Gross Weight: 3.0KG - Color Box dimension: 406 (W) * 359 (D) * 148 (H) mm |
| OS Support | - Windows 7, Windows 8.1, Windows 10, Linux |
| Warranty | - 2 Year limited warranty |