



469.00 EUR

incl. 19% VAT, plus [shipping](#)

- Intel Bay Trail !
- -40 - 70°C !
- 9-24V DC !
- All-aluminium !

Support: [Datasheet](#)

- Intel® Bay Trail SoC Processor (Default: J1900)
- Support 1 \* SO-DIMM DDR3L-1333MHz up to 8GB
- All-aluminum body, produced by casting process
- Operating Temperature: -40 ~ 70° C
- 9~24V DC-in (Lockable type)

|                |                                                                                                                                                                                                  |
|----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MB Model       | – MZ93-00B                                                                                                                                                                                       |
| Part No.       | – HBJC386Z9300-J19B<br>– HBJC386Z9300I-J19B (support M.2 ac WiFi)                                                                                                                                |
| BIOS           | – AMI Flash ROM                                                                                                                                                                                  |
| CPU/Chipset    | – Intel® Bay Trail SoC Processor (Default: J1900)                                                                                                                                                |
| Memory         | – Support 1 * SO-DIMM slots DDR3L-1333MHz up to 8GB                                                                                                                                              |
| Network        | – 2 * Intel i211-IT GbE                                                                                                                                                                          |
| Storage        | – 1 * M.2 M-key 2242/2280 slot (M2M, support SATA interface)                                                                                                                                     |
| Expansion      | – 1 * M.2 E-key 2230 (M2E, support USB 2.0/PCIex1 interface)<br>– 1 * M.2 B-key 3042 slot (M2B, support USB 3.0 interface)                                                                       |
| Rear Panel I/O | – 2 * RJ45<br>– 1 * DVI-I (Max. Resolution: 1920 * 1200@60Hz)<br>– 1 * HDMI (Max. Resolution: 1920 * 1200@60Hz)<br>– 1 * 8 bit GPIO<br>– 1 * Line out & MIC combo<br>– 1 * DC-in (Lockable type) |

|                 |                                                                                                                                                                                                                                                                                                 |
|-----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Front Panel I/O | <ul style="list-style-type: none"> <li>– 1 * Power SW + Power LED</li> <li>– 1 * HDD LED , 2 * LAN LED</li> <li>– 1 * SIM Card slot</li> <li>– 4 * COM (COM1_support RS485)</li> <li>– 4 * USB2.0</li> <li>– 2 * USB3.0</li> </ul>                                                              |
| Power Source    | <ul style="list-style-type: none"> <li>– Adapter / AC 90~240V input / DC12V-60W</li> <li>– MB : support DC 9~24V input</li> </ul>                                                                                                                                                               |
| Compliance      | <ul style="list-style-type: none"> <li>– CE, FCC, LVD, RoHS, ErP Ready</li> </ul>                                                                                                                                                                                                               |
| Temperature     | <ul style="list-style-type: none"> <li>– Operating Temperature: -40 ~ 70° C (Under the condition of using M.2 interface SSD)<br/>(The test environment is closed and windless)</li> <li>– Storage Temperature: -40 ~ 80° C</li> <li>– Humidity : 10% ~ 90% RH @40°C (non-condensing)</li> </ul> |
| Dimensions      | <ul style="list-style-type: none"> <li>– 185 (W) x 142 (D) x 60 (H) mm</li> </ul>                                                                                                                                                                                                               |
| OS Support      | <ul style="list-style-type: none"> <li>– Windows 10, Linux</li> </ul>                                                                                                                                                                                                                           |