



449.00 EUR
incl. 19% VAT, plus [shipping](#)

- STC-48750

Now you can power every PC in your truck. 750W power and P4 connector are giving you all possibilities !
The ATX connector has 24 pins.

| | |
|------------------------------|--|
| Dimensions | 170mm[W] × 150mm[L] × 86mm[H] |
| Weight | 3.0 kgs |
| Input Voltage Range | 37 - 71V VDC |
| Output Power maximum | 750W |
| Efficiency | 75% typical @48V DC Full Load |
| Output Power maximum (rails) | +3.3V : 35A +5.0V : 60A +12.0V : 48A |
| Over Power Protection | Peak power protected to 130%±10% of continuous rated power |
| Over Voltage Protection | +3.3V@4.5V, +5V@6V, +12V@15.6V |
| Short Circuit Protection | All output equipped with SCP (shutdown and latch off) |
| MTBF | 100 000 hours @max. Load, 48V DC & 25°C ambient |
| Safety Standards | Meet IEC60950-1, EN60950-1 |
| Operating Temperature | 0°C ~ +50°C full load |

| | |
|-----------------------|--|
| Storage Temperature / | -20°C~+80°C / 10%~90% RH. (Non condensing) |
| Humidity | |
| Cooling | 80x80x25 mm Fan x 1 pc, 70dBA @ Full Load |
| | 1x ATX 24Pin |
| | 1x +12V(P4) 4pin |
| | 2x 4pin HDD/DVD |
| Connectors | 1x 4pin FDD |
| | 4x Serial ATA |
| | 4x 8pin Process EPS |
| | 3x PCIe (6+2) |